

Honeywell

STP CAT6A KEYSTONE JACK

HONEYWELL Cat 6A STP Keystone Jack is a tool-less keystone suitable for 22-26 AWG solid as well as stranded wires. It has a metal body coated with nickel plating for longevity and sturdiness.

Features

- Suitable For 22-26 AWG Stranded And Solid Wire
- RJ45 8P 8C 50u Jacks
- Color Coded For T568A and T568B Wiring Schemes and Fit In High Density Keystone Patch Panel And on Face Plates
- Zinc Alloy (Casted Shell Covered With Nickel Plating)
- Complied With ANSI/TIA/EIA-568-C.2

Technical Specifications

Electrical:

1. Voltage Rating : 125 VAC RMS
2. Current Rating : 1.5 AMP
3. Contact Resistance : 100 Milliohms Max.
4. Insulation Resistance : 1000 Megohms Min. @ 500 VDC
5. Dielectric Strength : 750 VAC RMS 60Hz, 1 Min.

Environmental:

1. Storage : -40° To +70°
2. Operation : -10° To + 60°

Conform To TIA/EIA 568B Category 6A

Mates With Modular Plug Conforming To FCC Part 68, Subpart F.

Mechanical:


1. Housing Material : Zinc Alloy
2. Insert Material : Flame Retardant PC
3. PCB Material : FR-4 T=1.2 mm
4. Contact Material : Phosphor Bronze Stamp Pin T=0.35mm
5. IDC Contact Material : Phosphor Bronze T=0.35mm With Tin Plating
6. RJ45 Jack Life : 750 Times Min.
7. IDC Life : 200 Times Min.
8. Wire : AWG 22-24
9. TIA Cat 6A Perm. Link Test: Worst Pair NEXT Margin \geq 3.0dB
10. Retentiveness of Insertion Structure : 50N 60+/-5s



COPPER



CAT6A



STP



Ordering Information (Part Codes and Description)

No.	Part Code	Description
1	HC000326/CPR/C6A/STP/KJ	Cat6A STP Keystone Jack

www.honeywellconnection.com

The Honeywell trademark is used under license from Honeywell International Inc. Honeywell International Inc. makes no representation or warranties with respect to this product. This product is manufactured by Secure Connection Limited, Hong Kong. All trade names are registered trademarks of respective manufacturers listed. ©2021 Secure Connection Ltd., Hong Kong. All rights reserved